YG GROUP

Stock code: 603681

YG EVA Hot Melt Carton Sealing Solutions



World-Leading Adhesive Industry Solutions Provider

YG GROUP
Stock code: 603681

YG EVA ADVANTAGES

Superior Adhesion

Suitable for 3-layer, 5-layer, and 7-layer corrugated cartons, ensuring secure sealing.

Rapid Solidification

Achieves adhesion within seconds, improving production efficiency.

Stable Temperature Resistance

Adapts to storage and transportation environments from -10°C to 60°C, not prone to opening.



Excellent Fluidity

Compatible with automatic carton sealers, prevents nozzle clogging, and ensures smooth production.

Environmentally Friendly

No VOC emissions, compliant with food-grade and eco-friendly packaging requirements.

YG GROUP
Stock code: 603681

Hot Melt Adhesive – Carton Sealing Solutions



Logistics

Suitable for automatic carton sealers, meeting the high-efficiency sealing demands of the logistics.



E-commerce Packaging

Ensures carton integrity during transportation, preventing damage and opening.



Food Packaging

Meets food packaging safety requirements, odorless and non-toxic.



Industrial Packaging

Suitable for sealing heavy-duty cartons, ensuring long-term storage without adhesive failure.

- EVA hot melt adhesive is a high-efficiency and eco-friendly sealing adhesive, widely used in different industries.
- This product features rapid adhesion, excellent temperature resistance, and high strength stability, making it suitable for both automatic and manual carton sealing, providing efficient and reliable packaging solutions.

YG GROUP

Stock code: 603681

The YG-6 series products are hot melt adhesives for carton sealing, featuring a long open time, fast curing speed, good thermal stability, and excellent heat resistance.

YG-6110

Appearance	Light yellow granular solid	
Softening Point (°C, Ring & Ball Method)	Approx. 118	GB/T 4507-2014
Viscosity at 175°C	Approx. 1000 cps	GB/T 2794-1995
Open Time Curing Time Recommended Operating Temperature (°C)	3-5 seconds 2-5 seconds 165-180°C	

Standard Packaging: 25 kg/bag

YG-6112

Appearance	Light yellow granular solid	
Softening Point (°C, Ring & Ball Method)	Approx. 115	GB/T 4507-2014
Viscosity at 175°C	Approx. 1000 cps	GB/T 2794-1995
Open Time Curing Time Recommended Operating Temperature (°C)	5-8 seconds 4-7 seconds 165-180°C	

Standard Packaging: 25 kg/bag

Formulation Adjustment

Adjust formulation to suit different paper box materials

Color Selection

Adjust glue colors (transparent, white, yellow)

Physical Properties

Offer different viscosity & softening point opstions

Equipment Compatibility

Suitable for various automatic box sealing equipment

YG YG GROUP
Stock code: 603681



THANKS!

Shanghai Yongguan Adhesive Products Corp., Ltd.

ADD: No. 15 RD. KangGong, ZhuJiaJiao Industrial Zone, QingPu District, Shang Hai, China

TEL: +86-21 5983 5582 WEBSITE: www.yghotmelt.com E-MAIL: gmoffice1@ygtape.com