YGADM



PREMIUM SAV SERIES

POLYMERIC SAV WITH BUBBLE FREE TECH

Thickness:	100mic
Liner:	160gsm
Adhesive:	High tack solvent
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	Long-term weather resistance (3+ years), high adhesion
Application:	Motorcycle/Off-road Vehicle Graphics & Heavy-duty Outdoor Vehicle Decoration



MONOMERIC SAV WITH BUBBLE FREE TECH
(WHITE, BLACK, AND GRAY ADHESIVE)

Thickness:	100mic
Liner:	140gsm
Adhesive:	Solvent permanent/removable
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	High installation efficiency and user-friendly design, saving time and labor costs
Application:	Parcel Lockers & Vehicle Customization



TEL: +86-21 5983 5582 WEBSITE: www.ygadm.com E-MAIL: info@ygadm.com

SAV WITH DOUBLE-COATED LINER

Thickness:	100mic
Liner:	150gsm
Adhesive:	Solvent permanent/removable
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	Excellent stiffness & moisture resistance
Application:	Application scenarios with strict requirements for installation conditions



FLAME-RETARDANT SAV

Thickness:	100mic
Liner:	1400gsm
Adhesive:	Solvent removable
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	Flame-retardant (GB 8624 B1 certified)
Application:	Suitable for use in flame-retardant required environments



FLOW-PATTERN-FREE SAV

Thickness:	100mic、120mic
Liner:	150gsm
Adhesive:	High tack solvent
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	No flow marks/marbling Stretch-Resistant
Application:	Vehicle Advertising Applications Requiring HD Printing



HIGH GLOSS SAV, HIGH OPACITY SAV, HIGH TACK SAV

Thickness:	100mic
Liner:	140gsm
Adhesive:	Solvent permanent
Size:	0.914/1.07/1.27/1.37/1.52m*50m
Ink:	Solvent&UV
Feature:	Ultra-Glossy, Maximum Coverage, Super-Strong Stick
Application:	Public Transit Systems, Rail Transit Systems, Commercial Buildings, and Exhibition Events

