YG GROUP
Stock code: 603681

SINCE
2002
YG Group-Leading the
World in Stick-and-Solve

MASKING SOLUTIONS

Masking Tape | Washi Tape

YG GROUP
Stock code: 603681

About YG

YG Group, a global leader in adhesive solutions with over 20 years of industry expertise, is headquartered in Shanghai and operates five manufacturing bases—three in China (Shanghai, Jiangxi, and Shandong) and two overseas in **Malaysia** and **Vietnam**. Supported by three global operations centers in the U.S., and Mexico, YG Group delivers agile production, efficient logistics, and localized services worldwide.

Founded in Shanghai
In 2002

Main board Listing
In 2019

Total area
1 Million+ m²

Serving countries
110+

Employees
4000+

Serving customers
26000+



Shandong Production Base



U.S. Operation Center



Jiangxi Production Base



Shanghai Headquarter, R&D Center

Vietnam Production Base

Malaysia Production Base





Series	Classification	Product	Model	Adhesive	Thickness	Peel Strength	Tensile Strength	Temperature	UV Resistance	Color
					(μm)	(n/in)	(n/in)	(℃)	(Days)	
Masking Tape		General Purpose Masking Tape	MF1101	Rubber	110±10	≥5.0	≥60	60°C	/	Yellow 02
			MC1205	Rubber	120±10	≥5.0	≥70	60°C	/	White 01
			MAA130-b	Rubber	130±10	≥6.0	≥60	60°C	/	Yellow 02
		Medium Temperature Automotive Masking Tape	MLA140-i08	Rubber	140±10	≥5.0	≥70	80℃*30mins	/	Yellow 02
			MLA140-y10	Rubber	140±10	≥7.0	≥80	100℃*30mins	/	Yellow 04
			MLA150-y10	Rubber	150±10	≥7.0	≥80	100℃*30mins	/	Yellow 29 / Green 04
		High Temperature Automotive Masking Tape	MAA190-W	Rubber	190±15	≥7.5	≥90	160℃*30mins	/	Yellow 32
		Body Shop Masking Tape	MB501	Rubber	130±10	≥5.0	≥75	80℃*30mins	3	Yellow 02
			MA5401	Rubber	140±10	≥8.0	≥90	80℃*30mins	3	Yellow 02 / Orange 02
			MC5401	Rubber	140±10	≥5.5	≥70	100℃*30mins	3	Orange 02
			MB5490	Rubber	150±10	≥4.5	≥75	100℃*30mins	3	Yellow 33 / Green 04
			MA5801	Rubber	160±10	≥6.0	≥110	120℃*30mins	3	Orange 02
		Green Painter's Tape	MN1301	Rubber	130±10	≥2.0	≥90	60℃	15	Green 21
		Blue Painter's Tape	MLC120	Solvent	120±10	≥2.0	≥62	60℃	14	Blue 04 / Blue 03
			MLC140-zm4	Rubber	140±10	≥4.5	≥76	90℃	14	Blue 02 / Blue 04 / Blue 03
Washi Tape		Indoor General Washi Tape	MH1101	Solvent	100±10	≥3	≥70	80℃	3	Blue 21 / Yellow 23
			MH1202	Water-Based	110±10	≥2	≥75	80℃	7	Yellow 30 / Yellow 23
		Low Tack Washi Tape	MH2801	Rubber	80±10	≥2	≥70	100℃	/	Green 21 / Pink 21
		Sensitive Washi Tape	MH5001	Water-Based	90±10	≥2	≥65	60℃	15	Purple 22
		Japanese Washi Tape	MH5104	Water-Based	90±10	≥2	≥75	100℃*30min	30	Yellow 70
		Outdoor Washi Tape (15 Days)	HEC100	Water-Based	100±10	≥2	≥65	80℃*30min	15	Blue 21 / Pink 21 / Purple 22 / Yellow 23
		Outdoor Washi Tape (30 Days)	MH5002	Solvent	90±10	≥3	≥65	100℃*30min	30	Yellow 23
		High Temperature Resistance Washi Tape	MH6101	Solvent	100±10	≥3	≥75	150℃*30min	/	Yellow 70



Masking Tape

YG GROUP

Stock code: 603681

General Purpose Masking Tape



Features:

- Easy to tear by hand
- Lightweight and flexible
- Convenient for general use



Applications:

Ideal for interior decoration, DIY projects, packaging, and light-duty fixing tasks in home or light industrial settings.

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	Color
MF1101	Rubber	110±10	≥5.0	≥60	60°C	Yellow 02
MC1205	Rubber	120±10	≥5.0	≥70	60°C	White 01 Yellow 02
MAA130-b	Rubber	130±10	≥6.0	≥60	60°C	

YG GROUP

Stock code: 603681

Medium Temperature Automotive Masking Tape



Features:

- Temperature resistant from 80-100℃
- Strong adhesion with clean removal
- Suitable for curved and irregular surfaces
- Flexible and easy to tear
- Leaves no residue after baking for 30min



Applications:

Ideal for automotive painting, bundling, packaging, and decorative tasks in both indoor and outdoor environments.

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	Color
MLA140-i08	Rubber	140±10	≥5.0	≥70	80℃*30mins	Yellow 02 Yellow 04 Yellow 29 Green 04
MLA140-y10	Rubber	140±10	≥7.0	≥80	100℃*30mins	
MLA150-y10	Rubber	150±10	≥7.0	≥80	100℃*30mins	

YG GROUP

Stock code: 603681

High Temperature Automotive Masking Tape



Features:

- Heat resistant up to 160°C
- Clean removal without residue
- Easy to tear and apply
- Provides sharp paint lines
- Durable in industrial environments



Applications:

Ideal for automotive industry for masking during painting, refinishing, and other high-temperature applications requiring precision and reliability.

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	Color
MAA190-W	Rubber	190±15	≥7.5	≥90	160℃*30mins	Yellow 32

YG GROUP

Stock code: 603681

Body Shop Masking Tape



Features:

- UV resistant up to 3 days
- High peel strength prevents paint bleed
- Waterproof and weather-resistant
- Leaves no residue after removal
- Compatible with metal, plastic, and rubber surfaces



Applications:

Ideal for automotive painting, touch-ups, and surface protection during repairs, especially in short-term outdoor or UV-exposed environments.

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	UV Resistance (Days)	Color
MB501	Rubber	130±10	≥5.0	≥75	80℃*30mins	3	Yellow 02
MA5401	Rubber	140±10	≥5.5	≥70	100℃*30mins	3	Orange 02
MC5401	Rubber	140±10	≥8.0	≥90	80℃*30mins	3	Yellow 02 Orange 02
MB5490	Rubber	150±10	≥4.5	≥75	100℃*30mins	3	Yellow 33 Green 04
MA5801	Rubber	160±10	≥6.0	≥110	120℃*30mins	3	Orange 02

YG GROUP

Stock code: 603681

Green Painter's Tape





Features:

- Provides sharp paint lines
- Easy to remove without leaving residue
- Withstands direct outdoor sunlight for up to 15 days.
- Bonds quickly to the surface for instant painting

Applications:

Ideal for interior or exterior use on cured painted walls, wood trim, glass and metal

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	UV Resistance (Days)	Color
MN1301	Rubber	130±10	≥2.0	≥90	60℃	15	Green 21

YG GROUP

Stock code: 603681

Blue Painter's Tape



Features:



- 14-day UV resistance for long-term outdoor use
- Leaves no residue after removal
- Stable adhesion in various weather conditions
- Durable and easy to apply
- Suitable for smooth and textured surfaces

Applications:

Ideal for outdoor painting, construction, and automotive masking where long-lasting UV protection and clean removal are essential.

Model	Adhesive	Thickness (μm)	Peel Strength (n/in)	Tensile Strength (n/in)	Temperature (℃)	UV Resistance (Days)	Color
MLC120	Solvent	120±10	≥2.0	≥62	60 ℃	14	Blue 04, Blue 03
MLC140-zm4	Rubber	140±10	≥4.5	≥76	90 ℃	14	Blue 02, Blue 04, Blue 03



Washi Tape

YG GROUP

Stock code: 603681

Indoor General Washi Tape



Features:



- Medium adhesion with clearn removal;
- Writable with oil-based markers;
- Easy hand-tearability;
- Precise separation lines;

Applications:

Ideal for general home improvement and interior decoration

Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
General Tack	MH1101	80℃	3	Blue 21 Yellow 23	**Plastic:** PE (polyethylene); **Wood:** door frames, panels, flooring, wardrobes; **Others:** glass, tiles, plasterboard;
	MH1202	80℃	7	Yellow 30 Yellow 23	

YG GROUP

Stock code: 603681

Low Tack Washi Tape



Features:



- Clean removal;
- Low tack, repositionable, eco-friendly;
- Excellent lay-flat properties with no edge curling;

Applications:

Ideal for delicate surfaces such as artistic coatings, diatom mud, latex paint, and interior walls

Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
Low Tack	MH2801	100℃	/	Green 21 Pink 21	**Delicate Surfaces:** cardboard, sketch paper, A4 paper (slight roughness); **Wall Surfaces:** latex paint, newly painted surfaces, artistic finishes, diatomaceous earth coatings;

YG GROUP
Stock code: 603681

Sensitive Washi Tape



Features:

- Clean removal, easy hand-tearability;
- Medium-low tack, eco-friendly;
- Precise separation lines;



Applications:

Ideal for general home improvement and interior decoration

Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
Sensitive Washi Tape	MH5001	60℃	15	Purple 22	**Delicate Surfaces:** cardboard, sketch paper, A4 paper (slight roughness); **Wall Surfaces:** latex paint, newly painted surfaces, artistic finishes, diatomaceous earth coatings;

YG GROUP

Stock code: 603681

Japanese Washi Tape



Features:



- Made of Japanese washi paper
- Fine texture and high flexibility
- Good tensile and tear resistance
- Reliable UV resistance for outdoor use

Applications:

Ideal for indoor and outdoor renovation projects with UV resistance of 30 days

Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
Japanese Washi Tape	MH5104	100℃*30min	30	Yellow 70	**Metal:** steel plates, aluminum alloy windows, aluminum plates; **Plastics:** PE (polyethylene); **Wood:** door frames, wooden boards, flooring, wardrobes; **Others:** latex-painted walls, glass, plasterboard, tiles, wallpaper;

YG GROUP

Stock code: 603681

Outdoor Washi Tape (15 Days)



Features:

- Strong adhesion;
- Good temperature resistance;
- Solvent resistance and edge locking;
- Clean color separation, easy to apply;
- Reliable UV-resistant;



Applications:

Ideal for indoor and outdoor renovation projects with UV resistance of 15 days

Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
Outdoor Washi Tape (15 Days)	HEC100	80℃*30min	15	Blue 21 Purple 22 Pink 21 Yellow 23	**Metal:** steel plates, aluminum alloy windows, aluminum plates; **Plastics:** PE (polyethylene); **Wood:** door frames, wooden boards, flooring, wardrobes; **Others:** latex-painted walls, glass, plasterboard, tiles, wallpaper;

YG GROUP

Stock code: 603681

Outdoor Washi Tape (30 Days)







Features:

- Strong adhesion;
- Good temperature resistance;
- Solvent resistance and edge locking;
- Clean color separation, easy to apply;
- UV-resistant for long-term outdoor use;

Applications:

Ideal for indoor and outdoor renovation projects with UV resistance of 30 days


Classification	Model	Temperature (℃)	UV Resistance (Days)	Color	Applicable Materials
Outdoor Washi Tape (30 Days)	MH5002	100℃*30min	30	Yellow 23	**Metal:** steel plates, aluminum alloy windows, aluminum plates; **Plastics:** PE (polyethylene); **Wood:** door frames, wooden boards, flooring, wardrobes; **Others:** latex-painted walls, glass, plasterboard, tiles;

YG GROUP
Stock code: 603681

High Temperature Resistance Washi Tape



Features:





- Strong adhesion;
- High temperature resistance;
- Excellent solvent resistance and edge locking;
- Peels off smoothly without tearing or curling;
- Reliable UV-resistant;

Applications:

Ideal for high-temperature environments such as automotive and electronics industries

Classification	Model	Temperature (℃)	Color	Applicable Materials
High Temperature Resistance Washi Tape	MH6101	150℃*30min	Yellow 70	**Metals:** painted panels, steel plates, and other high-temperature application surfaces;